

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER
THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

[WIPO]

[Bar Code]

(43) International Publication Date

January 13, 2005 (01/13/2005)

PCT

(10) International Publication Number


WO 2005/003570 A1

- (51) International Patent Classification⁷: F15B 1/22, 1/24 (74) Representative: BARTELS AND PARTNER; Lange Strasse 51, 70174 Stuttgart (DE).
- (21) International Application No.: PCT/EP2004/002964
- (22) International Filing Date: March 20, 2004 (03/20/2004)
- (25) Language in which the international application was originally filed: German
- (26) Language in which the international application is published: German
- (30) Priority Data: 103 30 516.5 July 5, 2003 (07/05/2003) DE
- (71) Applicant (*for all designated states except the U.S.*): HYDAC TECHNOLOGY GMBH [DE/DE]; Industriegebiet, 66280 Sulzbach/Saar (DE).
- (72) Inventor; and
- (75) Inventor/Applicant (*U.S. only*): WEBER, Norbert [DE/DE]; Mozartstrasse 5, 66280 Sulzbach/Saar (DE).
- (81) Designated States (*unless indicated otherwise, for each available type of national protective right*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*unless indicated otherwise, for each available type of national protective right*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European Patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO,

[continued on next page]

(54) Title: HYDRAULIC ACCUMULATOR, ESPECIALLY PISTON-TYPE ACCUMULATOR

WO 2005/003570 A1



(57) Abstract: The invention relates to a hydraulic accumulator, especially a piston-type accumulator, comprising an accumulator housing (10) as well as at least one gas chamber (12) that is arranged therein and a fluid chamber (14) which are separated from each other via a separating element (16), particularly in the form of a piston. One free end of the accumulator housing (10) is sealed via a valve block (24) that is provided with a ball valve (28) which opens or blocks a fluid-guiding path (30) from the interior of the accumulator housing (10) towards the outside in the open position or closed position thereof such that the ball valve forms an integral part of the accumulator housing via the valve block and is thus accommodated in a compact manner within the hydraulic accumulator solution, also resulting in a reduction of the free fluid paths and therefore a reduction of tubing.

{Fortsetzung auf der nächsten Seite}

SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*Reference is made for an explanation of the two-letter
codes and the other abbreviations to the Guidance Notes
on Codes and Abbreviations in the front section of each
regular PCT Gazette edition.*

Published:

- *With International Search Report.*